

ERGENE[®]

CHEMICAL GENERAL MAINTENANCE

Technical Data Sheet

ER.814. GASKET REMOVER

ERGENE – ER. 814 removes gasket, decals, dried oils, varnish, adhesives, carbon deposits, shellac and similiat coatings from all types of metals, wood and plaster, adhesives to vertical surface. It is safe for use on most, type of metals and wood. Not safe for use on plastic tile, linoleum, synthetics or aluminium

Directions

Before using, protec all painted surface from over spray. Hold container 10 –12 inches from surfaces. Spray all areas to be stripped. Allow spray to set for 5 to 10 minutes. Scrape off softened gasket or paint with a putty knife. Thoroughly wash trated surface with water.

Cautions

Do not puncture or incinerate container. Store in direct sunlight or keep in place near source of heat temperature above 120°F (50°C). Avoid breathing vapour. Use with adequate ventilation. Wear eye protection while using. Avoid contact with skin. Use rubber gloves or other non porous hand protections while working with material. In case of accidental skin contact, flush with large quantities of water. If sprayed in eyes, flush thoroughly with water for 15 minutes. Get medical attention. Keep away from heat, sparks or open flame. Inhalation of high concentration of Mithylene Chloride vapour over a long period of time (years) has caused cancer in certain laboratory Animals. Deliberately concentrating and inhaling the vapour of the contents may be harmful or fatal if swallowed, do not induce vomiting. Call a physician immediately. Keep out of reach of children.

PACKAGING

- 12 Cans / box (500 ml / can)

